

PRODUCT NAME: AC 510 DRY FALL
 PRODUCT CODE: C-1137

HMIS CODES: H F R P

===== SECTION I - MANUFACTURERS IDENTIFICATION =====

MANUFACTURER'S NAME: INDURON PROTECTIVE COATINGS, INC.
 ADDRESS: 3333 RICHARD ARRINGTON Jr BLVD, N.
 BIRMINGHAM, ALABAMA 35234

EMERGENCY PHONE: (205) 324-9584 INFORMATION PHONE: (205) 324-9584
 DATE PRINTED: 4/6/2005 NAME OF PREPARER: WILLIAM G. SETSER

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
! CALCIUM CARBONATE TLV=10 MG/M3 (NUISANCE DUST)	471-34-1	N/A	37.29
* XYLENE (MIXED ISOMERS) PEL/TWA=100PPM, TLV/TWA=100PPM, TLV/STEL=150PPM	1330-20-7	5.1 68 F	10.79
VM&P NAPHTHA TLV/TWA=300 PPM, TLV/STEL=400 PPM	8032-32-4	5.2 20 C	8.31
! TITANIUM DIOXIDE TLV/TWA=10 MG/M3 TOTAL DUST OR 5 MG/M3 (NUISANCE DUST)	13463-67-7	N/A	7.56
MINERAL SPIRITS TLV/TWA=100PPM	8052-41-3	3.1 68 F	4.88
* * ETHYL BENZENE PEL/TWA=100PPM, TLV/TWA=100PPM, TLV/STEL=150PPM	100-41-4	5.1 68 F	1.52
METHYL ETHYL KETONE OXIME AIHA WEEL/TWA=10 PPM	96-29-7	2 20 C	.15
TOLUENE PEL/TWA=100PPM, TLV/TWA=100PPM, TLV/STEL=150PPM	108-88-3	24 68 F	.08

* INDICATES TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF 40 CFR 372.

! NOTE: PIGMENTS DO NOT NORMALLY POSE A DUST HAZARD IN COATINGS.

WARNING: DETECTABLE AMOUNTS OF CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR BIRTH DEFECTS OR REPRODUCTIVE HARM MAY BE PRESENT IN THIS PRODUCT.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

**SKIN CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN DRY AND DEFAT SKIN CAUSI
CRACKS, IRRITATION AND DERMATITIS.**

**EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE SEVERE IRRITATION,
TEARING, REDNESS AND BLURRED VISION.**

SENSITIZATION:

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: EARLY MODERATE CENTRAL NERVOUS
SYSTEM DEPRESSION AS EVIDENCED BY GIDDINESS, HEADACHE, DIZZINESS AND NAUSEA. IN
EXTREME CASES, UNCONSCIOUSNESS AND DEATH MAY OCCUR.**

**ORAL INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE GASTROINTESTINAL
IRRITATION, VOMITING, NAUSEA, AND DIARRHEA.**

EFFECTS OF OVEREXPOSURE:

INHALATION: DIZZINESS, BREATHING DIFFICULTY, HEADACHES, LOSS OF
COORDINATION.

EYE CONTACT: SEVERE IRRITATION, TEARING, REDNESS, AND BLURRED VISION.

SKIN CONTACT: CAN DRY AND DEFAT SKIN CAUSING CRACKS, IRRITATION AND
DERMATITIS.

INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA,
AND DIARRHEA.

CARCINOGENICITY: NTP?NO. IARC MONOGAPHS?NO.

OSHA REGULATED?YES.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: ALLERGY, ECZEMA, ASTHMA, OT
SKIN CONDITIONS.**

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: IRRIGATE WITH FLOWING WATER IMMEDIATELY AND CONTINUOUSLY FOR
15 MINUTES. CONSULT MEDICAL PERSONNEL.

SKIN CONTACT: IMMEDIATELY REMOVE CONTAMINATED CLOTHING. WASH CLOTHING
BEFORE REUSE. WASH OFF WITH SOAP AND FLOWING WATER OR SHOWER. IF SKIN
IRRITATION PERSISTS, SEE A PHYSICIAN.

INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN AND/OR TRANSPORT
TO A MEDICAL FACILITY IMMEDIATELY.

INHALATION OVEREXPOSURE: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE
MOUTH-TO-MOUTH RESUSCITATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN.
CALL A PHYSICIAN.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE ALL SOURCES
OF IGNITION. PROVIDE EXPLOSION PROOF VENTILATION. DIKE SPILL AREA AND TAKE UP
ON ABSORBENT MATERIAL. SHOVEL WITH NON-SPARKING TOOLS INTO CLOSABLE CONTAINER
FOR DISPOSAL. WEAR PROTECTIVE EQUIPMENT SPECIFIED BELOW. THOROUGHLY FLUSH
CONTAMINATED AREA WITH WATER.

WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL
REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: KEEP AWAY FROM HEAT, SPARKS
AND OPEN FLAME. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. AVOID BREATHING
VAPOR, MIST OR SPRAY. USE ONLY WITH GOOD VENTILATION. WASH AFTER HANDLING.
STORE IN CLOSED CONTAINERS IN COOL, WELL VENTILATED AREA.

===== SECTION VIII - SPECIAL PROTECTION INFORMATION =====

RESPIRATORY PROTECTION: ATMOSPHERIC CONCENTRATIONS SHOULD BE MAINTAINED BELOW TH
THRESHOLD LIMIT GUIDELINES PROVIDED. WHEN THESE CONCENTRATIONS CANNOT BE
MAINTAINED, RESPIRATORY PROTECTION IS REQUIRED. USE NIOSH/MSA APPROVED
CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICULATE,
GASEOUS AND VAPOR MATERIALS. IN CONFINED AREAS, USE A NIOSH/MSA APPROVED
POSITIVE-PRESSURE, SELF-CONTAINED BREATHING APPARATUS. WEAR RESPIRATORY
PROTECTION SUCH AS NIOSH/MSHA TC-21C-132 DUST/MIST RESPIRATOR WHEN SANDING,
GRINDING, BLASTING OR CUTTING THE DRY FILM OF THIS MATERIAL.

VENTILATION: WHERE POSSIBLE, PROVIDE GENERAL AND/OR LOCAL EXHAUST VENTILATION TO
CONTROL AIRBORNE LEVELS BELOW THE THRESHOLD LIMIT VALUES.

SKIN PROTECTION: FOR BRIEF CONTACT, NO PRECAUTIONS OTHER THAN CLEAN BODY-
COVERING CLOTHING SHOULD BE NEEDED. USE IMPERVIOUS GLOVES WHEN PROLONGED OR
FREQUENTLY REPEATED CONTACT MIGHT OCCUR

EYE PROTECTION: USE SPLASH PROOF CHEMICAL GOGGLES OR SAFETY GLASSES WITH
SIDE SHIELDS.

OTHER RECOMMENDED PROTECTIVE MEASURES: USE IMPERMEABLE CLOTHING, APRONS AND
PROTECTIVE COVERING WHENEVER POSSIBLE TO PREVENT SKIN CONTACT. WEAR HEAD
COVERING WHENEVER POSSIBLE.

RECOMMENDED HYGIENIC PRACTICES: WASH HANDS AND ARMS WITH SOAP AND WATER PRIOR TO EATING, DRINKING, SMOKING OR USING THE LAVATORY.

===== SECTION IX - DISCLAIMERS =====

THE INFORMATION CONTAINED HEREIN IS BASED PRIMARILY ON DATA PROVIDED US BY OUR SUPPLIERS, AND WE BELIEVE IT TO BE CORRECT. HOWEVER, INDURON COATINGS, INC. MAKES NO WARRENTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. INDURON ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.