



**PROTECTIVE COATINGS**

800 324 9584 | 3333 R. ARRINGTON N. • BHAM, AL 35234

## TECHNICAL DATA

### COLOR GUIDE

## COATING DATA

### DESCRIPTION:

A fugitive blue tint additive to aid in the uniform application of Induron Perma-Clear Fluorourethane and Indurethane 5000 Clear Coat.

### USE:

Add Color Guide to Indurethane 5000 Clear Coat or Perma-Clear Fluorourethane to temporarily provide contrast between the base coat color and the clear coat finish. Once the Clear Coat containing the Color Guide is applied, the blue tint will disappear within 24 hours. Bright U.V. light will accelerate the disappearance. Lower temperatures and indirect sunlight will slow the disappearance of the additive.

### COLORS:

Blue/Violet

### PACKAGING:

Color Guide 01X5000 Packet for one gallon kit of Indurethane 5000 Clear Coat or Perma-Clear Fluorourethane.

### LIMITATIONS:

Not for use in other paints or coatings.  
Shelf Life - 12 months between 20°F and 110°F.

## APPLICATION DATA

### MIXING INSTRUCTIONS:

For a one gallon kit of Induron Perma-Clear Fluorourethane or Indurethane 5000 Clear Coat, add the entire contents of a packet of Color Guide 01X5000 to a one gallon container while under agitation. Mix thoroughly. To this mixture, add one Activator. Continue agitation until thoroughly mixed. Do not use more than one packet of Color Guide per gallon of Clear Coat. Not for use with other paints or coatings. Read caution statements on back of packet. Patent Number 5,548,010

For a five gallon kit of Induron Perma-Clear Fluorourethane or Indurethane 5000 Clear Coat, add the entire contents of five packets of Color Guide 01X5000 to a five gallon container while under agitation. Mix thoroughly. To this mixture, add one Activator. Continue agitation until thoroughly mixed. Not for use with other paints or coatings. Read caution statements on back of packet. Patent Number 5,548,010

### PHYSICAL DATA:

VOLUME SOLIDS: 3.1% ± .1%  
WEIGHT PER GALLON: 6.85 ± .1 lbs per gallon

### SAFETY DATA:

This product is formulated free of lead, chromates, mercury or other toxic pigments. See product label for safety and health information. Individual Material Safety Data Sheets are available upon request.  
505