

SAFETY DATA SHEET

SECTION 1 - MANUFACTURER'S IDENTIFICATION

Product Name: MORTARCHEM PART A Product Code: H-8070

Manufacturer's Name: Induron Protective Coatings, LLC
Address: 3333 Richard Arrington Blvd. N.
Birmingham, Alabama 35234

Emergency Phone: 1-800-424-9300
Information Phone: (205)324-9584



Section 2 - Composition / Information on Ingredients

GHS Ratings:

Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Skin sensitizer	1	Skin sensitizer

GHS Hazards

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation

GHS Precautions

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash equipment and contaminated skin thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P321	Wash contaminated skin, follow Physician's instructions for treatment.
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P332+P313	If skin irritation occurs: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P501	Dispose of contents/container in accordance to appropriate regulations and laws.

Signal Word: Warning



Preexisting skin, eye, and respiratory disorders may be aggravated by exposure to this product. Impaired kidney and liver functions from preexisting disorders may be aggravated by exposure to this product.

Kidney damage may be evidenced by changes in urine output, urine appearance, or edema (swelling from fluid retention). Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

Section 3 - Hazards Identification

Chemical Name	CAS number	Weight Concentration %
GLYCIDYL EPOXY	25085-99-8	20.00% - 30.00%

Section 4 - First Aid Measures

INHALATION - If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation; call a physician. Administer oxygen if a qualified operator is available.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water.

INGESTION - If material is ingested, seek immediate medical attention. If vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs.

Notes to Physician: No data found

Section 5 - Fire Fighting Measures

Flash Point: 142 C (288 F)

LEL:

UEL:

Non Combustible Product

EXTINGUISHING MEDIA: Use carbon dioxide (CO₂), "alcohol" foam, dry chemical systems, water spray, normal water extinguishing.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product may contain vapors that will flash, but will not catch on fire.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon and hydrocarbons

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure. Use water spray to cool unopened containers.

Fire Equipment: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

SMALL SPILLS: Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes. Wet absorbant materials with water to prevent spontaneous combustion with alkyd type formulas.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes. Wet absorbant with water for alkyd type spills.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Prevent from freezing. Do not store above 120 F (49 C).

Store only in original containers.

REGULATORY REQUIREMENTS: No data found.

Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
GLYCIDYL EPOXY 25085-99-8	Not Established	Not Established	Not Established

ENGINEERING: Ensure processing (curing) ovens are properly vented to prevent the introduction of processing fumes into the workplace. Use explosion-proof equipment and good manufacturing practice.

VENTILATION: Use only with adequate ventilation, i.e., ventilation in compliance with occupational exposure limits.

ADMINISTRATIVE CONTROLS: No data found.

PROTECTIVE EQUIPMENT: Wear splash goggles. If extra protection is required, wear a face shield over the splash goggles. Face shields are effective only if worn in addition to splash goggles.

Wear a chemical-resistant, butyl-rubber apron and other protective clothing, as deemed appropriate, to avoid skin contact with material.

Wear chemical-resistant gloves (butyl rubber or neoprene). Protective gloves should be inspected frequently and discarded when they exhibit cuts, tears, pinholes, or signs of excessive wear.

CONTAMINATED EQUIPMENT: Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

Viscosity: N/A	Coating VOC Lb/Gal 0.00
Appearance: N/A	Odor: N/A
Vapor Pressure: N/A	Odor threshold: N/A
Vapor Density: N/A	pH: N/A
DENSITY 8.59	Melting point: N/A
Freezing point: N/A	Solubility: N/A
Boiling range: 100°C	Flash point: 288 F, 142 C
Evaporation rate: N/A	Flammability: N/A
Explosive Limits: N/A	Partition coefficient (n-octanol/water): N/A
Autoignition temperature: N/A	Decomposition temperature: N/A

Section 10 - Stability and Reactivity

Stability: This product is stable under normal storage and handling.

STABLE

Components of this mixture are incompatible with the following materials: Strong acids and bases can cause

coagulation of the latex and failure of the product

This mixture is likely to exhibit the following combustion products: aliphatics and carbon oxides.

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Routes of Entry:

Ingestion

Exposure to this material may affect the following organs:

Effects of Overexposure

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
-------------------	--------------------	-----------------	--------------------------

Section 12 - Ecological Information

Ecological information: .

Component Ecotoxicity

Section 13 - Disposal Considerations

As the US EPA, state, regional, and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all the requirements which affect you. Dispose of the hazardous waste at a properly licensed and permitted disposal site or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream." Refer to Title 40 of the Code of Federal Regulations, Part 261 (40 CFR 261). This part of the Code identifies solid wastes which are subject to regulation under various sections of the Code and which are subject to the notification requirements of Section 3010 of the Resource Conservation and Recovery Act (RCRA).

Section 14 - Transport Information

Section 14 - Transport Information

Not regulated by CFR 49.172.1

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	PAINT	NA	NA	NA
IATA	PAINT	NA	NA	NA

15: Regulatory Information

Country

Regulation

All Components Listed

EU Risk Phrases

Safety Phrase

- None


16: OTHER INFORMATION

Hazardous Material Information System (HMIS)

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

HMIS & NFPA Hazard Rating
Legend
* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH

National Fire Protection Association (NFPA)



Reviewer Revision

Date Prepared: 10/13/2016

SAFETY DATA SHEET

SECTION 1- MANUFACTURER'S IDENTIFICATION

Product Name: MORTARCHEM PART B Product Code: Q-8071

Trade Name: MORTARCHEM

Manufacturer's Name: Induron Protective Coatings, LLC
Address: 3333 Richard Arrington Blvd. N.
Birmingham, Alabama 35234

Emergency Phone: 1-800-424-9300

Information Phone: (205)324-9584

Section 2 - Composition / Information on Ingredients

GHS Ratings:

Oral Toxicity	Acute Tox. 4	Oral>300+<=2000mg/kg
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5

GHS Hazards

H302	Harmful if swallowed
H318	Causes serious eye damage

GHS Precautions

P264	Wash equipment and contaminated skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P310	Immediately call a POISON CENTER or doctor/physician
P330	Rinse mouth
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P501	Dispose of contents/container in accordance to appropriate regulations and laws.

Signal Word: Danger



Preexisting skin, eye, and respiratory disorders may be aggravated by exposure to this product. Impaired kidney and liver functions from preexisting disorders may be aggravated by exposure to this product.

Kidney damage may be evidenced by changes in urine output, urine appearance, or edema (swelling from fluid retention). Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

Section 3 - Hazards Identification

Chemical Name	CAS number	Weight Concentration %

Section 4 - First Aid Measures

INHALATION - If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation; call a physician. Administer oxygen if a qualified operator is available.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water.

INGESTION - If material is ingested, seek immediate medical attention. If vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs.

Notes to Physician: No data found

Section 5 - Fire Fighting Measures

Flash Point: 104 C (219 F)

LEL:

UEL:

Non Combustible Product

EXTINGUISHING MEDIA: Use carbon dioxide (CO₂), "alcohol" foam, dry chemical systems, water spray, normal water extinguishing.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product may contain vapors that will flash, but will not catch on fire.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon and hydrocarbons

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure. Use water spray to cool unopened containers.

Fire Equipment: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

SMALL SPILLS: Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes. Wet absorbant materials with water to prevent spontaneous combustion with alkyd type formulas.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes. Wet absorbant with water for alkyd type spills.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not

in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Prevent from freezing. Do not store above 120 F (49 C).

Store only in original containers.

REGULATORY REQUIREMENTS: No data found.

Section 8 - Exposure Controls / Personal Protection			
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
	Not Established	Not Established	Not Established

ENGINEERING: Ensure processing (curing) ovens are properly vented to prevent the introduction of processing fumes into the workplace. Use explosion-proof equipment and good manufacturing practice.

VENTILATION: Use only with adequate ventilation, i.e., ventilation in compliance with occupational exposure limits.

ADMINISTRATIVE CONTROLS: No data found.

PROTECTIVE EQUIPMENT: Wear splash goggles. If extra protection is required, wear a face shield over the splash goggles. Face shields are effective only if worn in addition to splash goggles.

Wear a chemical-resistant, butyl-rubber apron and other protective clothing, as deemed appropriate, to avoid skin contact with material.

Wear chemical-resistant gloves (butyl rubber or neoprene). Protective gloves should be inspected frequently and discarded when they exhibit cuts, tears, pinholes, or signs of excessive wear.

CONTAMINATED EQUIPMENT: Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 9 - Physical and Chemical Properties
--

This mixture typically exhibits the following properties under normal circumstances:

<p>Viscosity: N/A</p> <p>Appearance: N/A</p> <p>Vapor Pressure: N/A</p> <p>Vapor Density: N/A</p> <p>DENSITY: 9.00</p> <p>Freezing point: N/A</p> <p>Boiling range: 100°C</p> <p>Evaporation rate: N/A</p> <p>Explosive Limits: N/A</p> <p>Autoignition temperature: N/A</p>	<p>Coating VOC Lb/Gal: 0.00</p> <p>Odor: N/A</p> <p>Odor threshold: N/A</p> <p>pH: N/A</p> <p>Melting point: N/A</p> <p>Solubility: N/A</p> <p>Flash point: 219 F, 104 C</p> <p>Flammability: N/A</p> <p>Partition coefficient (n-octanol/water): N/A</p> <p>Decomposition temperature: N/A</p>
--	---

Section 10 - Stability and Reactivity

Stability: This product is stable under normal storage and handling.

STABLE

Components of this mixture are incompatible with the following materials: Strong acids and bases can cause coagulation of the latex and failure of the product

This mixture is likely to exhibit the following combustion products: aliphatics and carbon oxides.

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Routes of Entry:

Ingestion

Exposure to this material may affect the following organs:

Effects of Overexposure

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

Section 12 - Ecological Information

Ecological information: .

Section 13 - Disposal Considerations

As the US EPA, state, regional, and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all the requirements which affect you. Dispose of the hazardous waste at a properly licensed and permitted disposal site or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream." Refer to Title 40 of the Code of Federal Regulations, Part 261 (40 CFR 261). This part of the Code identifies solid wastes which are subject to regulation under various sections of the Code and which are subject to the notification requirements of Section 3010 of the Resource Conservation and Recovery Act (RCRA).

Section 14 - Transport Information

Section 14 - Transport Information

Not regulated by CFR 49.172.1

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	PAINT	NA	NA	NA
IATA	PAINT	NA	NA	NA

15: Regulatory Information

Country

Regulation

All Components Listed

EU Risk Phrases

Safety Phrase


- None

Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

HMIS & NFPA Hazard Rating
Legend
* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH

National Fire Protection Association (NFPA)



Reviewer Revision

Date Prepared: 10/18/2016

SAFETY DATA SHEET

SECTION 1- MANUFACTURER'S IDENTIFICATION

Product Name: MORTARCHEM PART C Product Code: H-8072

Manufacturer's Name: Induron Protective Coatings, LLC
Address: 3333 Richard Arrington Blvd. N.
Birmingham, Alabama 35234

Emergency Phone: 1-800-424-9300
Information Phone: (205)324-9584

Section 2 - Composition / Information on Ingredients

GHS Ratings:

Skin corrosive 3 Reversible adverse effects in dermal tissue, Draize score:
>= 1.5 < 2.3
Eye corrosive 2A Eye irritant: Subcategory 2A, Reversible in 21 days

GHS Hazards

GHS Precautions

Signal Word:



Not applicable

Not applicable

Section 3 - Hazards Identification

Chemical Name	CAS number	Weight Concentration %
Cement, portland, chemicals	65997-15-1	

Section 4 - First Aid Measures

INHALATION - Wear dusk mask if sanding, avoid smoke if burning.

EYE CONTACT - NOT APPLICABLE

SKIN CONTACT - AVOID ABRASION

INGESTION -NOT APPLICABLE

Notes to Physician: No data found

Section 5 - Fire Fighting Measures

Flash Point: N/A

LEL:

UEL:

EXTINGUISHING MEDIA: Use carbon dioxide (CO₂), "alcohol" foam, dry chemical, or water spray/water fog extinguishing systems.

UNUSUAL FIRE OR EXPLOSION HAZARDS: NONE

HAZARDOUS COMBUSTION PRODUCTS: See section 10 for a list of hazardous decomposition products for this mixture.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: NOT APPLICABLE

SMALL SPILLS: Not Applicable

LARGE SPILLS: Not Applicable.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: KEEP AWAY FROM FLAMES

STORAGE. Do not store above 120 F (49 C).

REGULATORY REQUIREMENTS: No data found.

Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Cement, portland, chemicals 65997-15-1	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	1 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	NIOSH: 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust)

ENGINEERING: No special handling required

VENTILATION: High temperature storage requires ventilation. Temperatures of over 120°F should be avoided if possible.

ADMINISTRATIVE CONTROLS: No data found.

PROTECTIVE EQUIPMENT: Wear gloves when handling.

CONTAMINATED EQUIPMENT: Not applicable

Section 9 - Physical and Chemical Properties

This coating has the following properties.

Appearance DRY PAINT FILM Physical State SOLID Evaporation Rate NOT APPLICABLE Specific Gravity (SG) 1.081	Odor SLIGHT OR NONE Vapor Density NOT AVAILABLE Coating VOC Lb/Gal 0.00
---	--

Section 10 - Stability and Reactivity

Stability: Stable
STABLE

Not applicable

This mixture is likely to exhibit the following combustion products:
Aromatic decomposition byproducts from Coal Tar Pitch.

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

The product is non hazardous other than sanding dust and combustion by product during fire.

Routes of Entry: Not applicable

Ingestion

Exposure to this material may affect the following organs:

Eyes Skin Respiratory System

Effects of Overexposure

Carcinogenicity: Sanding dust and combustion by products could have cancer causing components. Non hazardous as is.

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
-------------------	--------------------	-----------------	--------------------------

Section 12 - Ecological Information

Ecological information: No data found.

Component Ecotoxicity

Section 13 - Disposal Considerations

As the US EPA, state, regional, and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all the requirements which affect you. Dispose of the hazardous waste at a properly licensed and permitted disposal site or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream." Refer to Title 40 of the Code of Federal Regulations, Part 261 (40 CFR 261). This part of the Code identifies solid wastes which are subject to regulation under various sections of the Code and which are subject to the notification requirements of Section 3010 of the Resource Conservation and Recovery Act (RCRA).

Section 14 - Transport Information

Section 14 - Transport Information

No special hazards.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	NA	NA	NA	NA
IATA	NA	NA	NA	NA

MASSACHUSETTS RIGHT TO KNOW

65997-15-1 Cement, portland, chemicals 40 to 50 %

NEW JERSEY RIGHT TO KNOW

65997-15-1 Cement, portland, chemicals 40 to 50 %

PENNSYLVANIA RIGHT TO KNOW

65997-15-1 Cement, portland, chemicals 40 to 50 %

Country

Regulation

All Components Listed

EU Risk Phrases

Safety Phrase

- None

[Empty rectangular box]

Hazardous Material Information System (HMIS)

HEALTH	*	1
FLAMMABILITY		0
PHYSICAL HAZARD		0
PERSONAL PROTECTION	E	

HMIS & NFPA Hazard Rating

Legend

* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

National Fire Protection Association (NFPA)



Reviewer Revision

Date Prepared: 10/14/2016