

# SAFETY DATA SHEET

## Section 1: Manufacturer's Identification

Product Name: PERMATUFF WALL COATING Product Code: A4-1384W

Manufacturer's Name: Induron Protective Coatings, LLC  
Address: 3333 Richard Arrington Blvd. N.  
Birmingham, Alabama 35234

Emergency Phone: 1-800-424-9300  
Information Phone: (205)324-9584

## Section 2 : Composition / Information on Ingredients

### GHS Ratings:

Dermal Toxicity	Acute Tox. 3	Dermal>200+<=1000mg/kg
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Respiratory sensitizer	1	Respiratory sensitizer
Skin sensitizer	1	Skin sensitizer
Mutagen	1B	Known to produce heritable mutations in human germ cellsSubcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Reproductive toxin	1B	Presumed, Based on experimental animals

### GHS Hazards

H311	Toxic in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H340	May cause genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child

### GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash equipment and contaminated skin thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required
P285	In case of inadequate ventilation wear respiratory protection
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P321	Wash contaminated skin, follow Physician's instructions for treatment.
P322	Specific measures Remove contaminated clothing and protective equipment.
P361	Remove/Take off immediately all contaminated clothing
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse
P302+P352	IF ON SKIN: Wash with soap and water

P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician.
P405	Store locked up
P501	Dispose of contents/container in accordance to appropriate regulations and laws.

**Signal Word: Danger**



This product can be a skin and eye sensitizer. The material should be washed from skin or flushed from eyes immediately. Contaminated clothing should be removed. Wear proper protective equipment. Any other acute toxicological information can be found in section 11. Approximately 2% of the population can develop skin sensitivity with increasing inflammation and allergic reactions with repeated exposure.

**Section 3 : Hazards Identification**

Chemical Name	CAS number	Weight Concentration %
Titanium Dioxide Colorant	13463-67-7	20.00% - 30.00%
Diglycidyl Ether of Bisphenol A	25068-38-6	20.00% - 30.00%
Benzyl Alcohol	100-51-6	5.00% - 10.00%
Kaolin	1332-58-7	1.00% - 5.00%
STODDARD SOLVENT	8052-41-3	0.10% - 1.00%
Naptha(Pet), light arom.	64742-95-6	0.10% - 1.00%
2-ETHYL BENZENE	100-41-4	0.10% - 1.00%

**Section 4: First Aid Measures**

Move the exposed person to fresh air. If vapors are still present the rescuer should wear the appropriate mask. If breathing is irregular or arrest occurs use artificial respiration by trained personnel. Loosen tight fitting clothing, Get medical aid immediately.

Immediately flush eyes with plenty of water for at least 15 minutes. Regularly lift upper and lower eyelids during flushing. Remove contact lenses. Get medical aid.

Flush contaminated skin with water. Remove contaminated cloths, avoiding skin contact while doing so. Get medical attention. Clean contaminated shoes thoroughly before reuse.

Wash mouth out thoroughly. Do not induce vomiting unless directed by medical personnel. Get medical attention

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been inhaled or ingested.

**Section 5: Fire Fighting Measures**

Flash Point: 99 C (210 F)

LEL: 1.00

UEL: 13.00

For flammable liquid: Can burst from pressure if in sealed container and heated, with risk of subsequent explosion. Vapors are heavier than air, can spread on ground and collect in low lying areas. Runoff to a collection area can create a fire or explosion hazard.

Dry Chemical, CO2, water spray)(fog), or foam. Do not use water jet.

Isolate scene removing persons not trained if there is a fire. Move containers from fire area if there is no risk. Use water spray to keep fire exposed containers cool

Decomposition products may include the following materials: Carbon Oxides.

Fire fighters should wear appropriate protective equipment and well-ventilated breathing apparatus.

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam. Do not use water jet.

### Section 6: Accidental Release Measures

No action should be taken with untrained personnel. Evacuate surrounding areas. Do not touch or walk through spill.

Shut off all ignition sources. Provide adequate ventilation. Use appropriate protective equipment. Do not breathe dust, mist, or vapor.

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble, or absorb with inert dry material and place in appropriate waste container. Dispose via licensed waste disposal.

Stop leak if without risk. Move containers from area. Approach from upwind. Prevent run off to water source, basements, sewers, or confined areas. Contain and collect spillage with non combustible, absorbent materials, sand, vermiculite, diatomic earth and dispose by local regulation. Use spark-proof tools and explosion proof equipment.

### Section 7: Handling and Storage

Use appropriate personal protective equipment. No eating, drinking, or smoking in areas of use. Persons with a history of skin sensitization should not be employed in any process in which this product is used. Avoid exposure during pregnancy. Do not ingest. Use adequate ventilation or respirator. Keep in appropriate container avoiding open flames, sparks or other ignition sources. Use explosion proof equipment and non sparking tools. Use proper grounding procedures.

Store in designated flammable liquid storage areas. Protect from direct sunlight in dry, cool ventilated areas. Keep food and drink away from area. Eliminate all ignition sources. Opened containers must be carefully resealed and kept upright.

Do not use unlabeled containers. Use appropriate containment.

### Section 8: Exposure Controls/ Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Titanium Dioxide Colorant 13463-67-7	15 mg/m <sup>3</sup> TWA (total dust)	10 mg/m <sup>3</sup> TWA	Not Established
Diglycidyl Ether of Bisphenol A 25068-38-6	Not Established	Not Established	Not Established
Benzyl Alcohol 100-51-6	Not Established	Not Established	Not Established
Kaolin 1332-58-7	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	2 mg/m <sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	NIOSH: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust)
STODDARD SOLVENT 8052-41-3	500 ppm TWA; 2900 mg/m <sup>3</sup> TWA	100 ppm TWA	NIOSH: 350 mg/m <sup>3</sup> TWA 1800 mg/m <sup>3</sup> Ceiling (15 min)
Naptha(Pet), light arom. 64742-95-6	Not Established	Not Established	Not Established
2-ETHYL BENZENE 100-41-4	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m <sup>3</sup> TWA 125 ppm STEL; 545 mg/m <sup>3</sup> STEL

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or

other engineering controls to meet exposure to airborne cotaminates above statutory limits. Use appropriate controls to keep concentration below explosive limits.

Ensure adequate ventilation by standard emission testing procedures, Use appropriate respiratory equipment when needed.

Assure safety training of operators in regards to handling liquids and vapors. Follow local regulatory rules of exposure control using air purifying or air supplied mask as needed.

Use appropriate protective equipment according to OSHA and NAFTA standards and labeling. Ensure eye wash stations and safety showers are available.

Wash contaminated gear and clothing before reuse.

### Section 9: Physical and Chemical Properties

<p><b>Appearance:</b> N/A</p> <p><b>Vapor Pressure:</b> 0.073 mmHg</p> <p><b>Vapor Density:</b> 3.7</p> <p><b>DENSITY:</b> 14.56</p> <p><b>Freezing point:</b> N/A</p> <p><b>Boiling range:</b> 205°C</p> <p><b>Evaporation rate:</b> N/A</p> <p><b>Explosive Limits:</b> N/A</p> <p><b>Autoignition temperature:</b> N/A</p> <p><b>Viscosity:</b> N/A</p>	<p><b>Odor:</b> N/A</p> <p><b>Odor threshold:</b> N/A</p> <p><b>pH:</b> N/A</p> <p><b>Melting point:</b> N/A</p> <p><b>Solubility:</b> N/A</p> <p><b>Flash point:</b> 210 F, 99 C</p> <p><b>Flammability:</b> N/A</p> <p><b>Partition coefficient (n-octanol/water):</b> N/A</p> <p><b>Decomposition temperature:</b> N/A</p> <p><b>Coating VOC Lb/Gal:</b> 0.93</p>
---	--

### Section 10: Stability and Reactivity

These materials are stable. Under normal conditions of storage and use hazardous reactions or polymerization will not occur.

Avoid all source of ignitions, sparks or flames. Do not allow vapor to accumulate in low lying areas.

STABLE

Do not expose to strong oxidizing agents, strong acids, or aliphatic amines.

Under normal use, no hazardous decomposition products are produced.

Hazardous polymerization will not occur.

### Section 11: Toxicological Information

#### Mixture Toxicity

Dermal Toxicity LD50: 720mg/kg

Inhalation Toxicity LC50: 157mg/L

Routes of Entry:

#### Ingestion

Exposure to this material may affect the following organs:

Eyes

Kidneys

Central Nervous System

Skin

Respiratory System

#### Effects of Overexposure

**Carcinogenicity:** The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

CAS Number

Description

% Weight

Carcinogen Rating

13463-67-7	Titanium Dioxide Colorant	20 to 30%	Titanium Dioxide Colorant: NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed
100-41-4	2-ETHYL BENZENE	.1 to 1.0%	2-ETHYL BENZENE: IARC: Possible human carcinogen OSHA: listed
64742-95-6	Naptha(Pet), light arom.	.1 to 1.0%	Naptha(Pet), light arom.: EU REACH: Present (P)
8052-41-3	STODDARD SOLVENT	.1 to 1.0%	STODDARD SOLVENT: EU REACH: Present (P)

### Section 13: Ecological

No known significant effects or critical hazards.

#### Component Ecotoxicity

Benzyl Alcohol	96 Hr LC50 Pimephales promelas: 460 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 10 mg/L [static] 48 Hr EC50 water flea: 23 mg/L
Naptha(Pet), light arom.	96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L 48 Hr EC50 Daphnia magna: 6.14 mg/L
2-ETHYL BENZENE	96 Hr LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static] 48 Hr EC50 Daphnia magna: 1.8 - 2.4 mg/L 72 Hr EC50 Pseudokirchneriella subcapitata: 4.6 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: >438 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L [static]; 96 Hr EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static]

### Section 13: Disposal Considerations

Minimize the generation of waste whenever possible. Dispose by licensed waste disposal contractor. Comply with local, regional, and federal disposal regulations and legislation.

### Section 14: Transport Information

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	PAINT			
IATA	PAINT			

### Section 15: Regulatory Information

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- 100-41-4 2-ETHYL BENZENE 0.1 to 1.0 %
- 13463-67-7 Titanium Dioxide Colorant 20 to 30 %

HAZARDOUS AIR POLLUTANTS

100-41-4 2-ETHYL BENZENE

HAZARDOUS SUBSTANCE/CHEMICALS/POLLUTANTS

- None

MASSACHUSETTS RIGHT TO KNOW

- 100-41-4 2-ETHYL BENZENE 0.1 to 1.0 %
- 8052-41-3 STODDARD SOLVENT 0.1 to 1.0 %
- 1332-58-7 Kaolin 1 to 5 %
- 100-51-6 Benzyl Alcohol 5 to 10 %
- 13463-67-7 Titanium Dioxide Colorant 20 to 30 %

NEW JERSEY RIGHT TO KNOW

- 100-41-4 2-ETHYL BENZENE 0.1 to 1.0 %
- 8052-41-3 STODDARD SOLVENT 0.1 to 1.0 %
- 1332-58-7 Kaolin 1 to 5 %
- 13463-67-7 Titanium Dioxide Colorant 20 to 30 %

PENNSYLVANIA RIGHT TO KNOW

- 100-41-4 2-ETHYL BENZENE 0.1 to 1.0 %
- 8052-41-3 STODDARD SOLVENT 0.1 to 1.0 %
- 1332-58-7 Kaolin 1 to 5 %
- 100-51-6 Benzyl Alcohol 5 to 10 %
- 13463-67-7 Titanium Dioxide Colorant 20 to 30 %

- None

CHEMICAL LIST FOR SARA 311

- None

CHEMICAL LIST FOR SARA 311/312

- 100-51-6 Benzyl Alcohol

CHEMICAL LIST FOR SARA 313

- 100-41-4 2-ETHYL BENZENE

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
<b><u>EU Risk Phrases</u></b>		
<b><u>Safety Phrase</u></b>		

- None

**Section 16: Other Information**

HMIS and NAFTA rating are on a 0 to 4 rating scale with 0 minimal hazard, and 4 represent significant danger or hazard.

**Hazardous Material Information System (HMIS)**

**National Fire Protection Association (NFPA)**

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>1</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>C</b>

**HMIS & NFPA Hazard Rating**

**Legend**


\* = Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH



The information provided herein was believed by Induron Protective Coating to be accurate and reliable, but the user is responsible to comply with all laws and procedures whether included or not. Induron makes no warranty expressed or implied concerning the accuracy of the information except the product will comply with Induron specifications.

Reviewer Revision

Date Prepared: 9/29/2016

# SAFETY DATA SHEET

## Section 1: Manufacturer's Identification

Product Name: PERMATUFF ACTIVATOR Product Code: Q4-1375

Manufacturer's Name: Induron Protective Coatings, LLC  
Address: 3333 Richard Arrington Blvd. N.  
Birmingham, Alabama 35234

Emergency Phone: 1-800-424-9300  
Information Phone: (205)324-9584

## Section 2: Composition / Information on Ingredients

### GHS Ratings:

Oral Toxicity	Acute Tox. 4	Oral>300+<=2000mg/kg
Inhalation Toxicity	Acute Tox. 4	Gases>2500+<=5000ppm, Vapors>10+<=20mg/l, Dusts&mists>1+<=5mg/l
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Skin sensitizer	1	Skin sensitizer

### GHS Hazards

H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled

### GHS Precautions

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash equipment and contaminated skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product
P271	Use only outdoors or in a well-ventilated area
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P310	Immediately call a POISON CENTER or doctor/physician
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P321	Wash contaminated skin, follow Physician's instructions for treatment.
P330	Rinse mouth
P363	Wash contaminated clothing before reuse
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P302+P352	IF ON SKIN: Wash with soap and water
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P501	Dispose of contents/container in accordance to appropriate regulations and laws.

Signal Word: Danger





**Section 3 : Hazards Identification**

Chemical Name	CAS number	Weight Concentration %
Benzyl Alcohol	100-51-6	40.00% - 50.00%
Modified Polyamine	1477-55-0	20.00% - 30.00%

**Section 4: First Aid Measures**

Remove to fresh air, seek medical attention.  
Immediately flush eyes with water for at least 15 min. Seek medical attention.  
Immediately washes with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes. Seek medical attention.  
Do not induce vomiting unless directed by medical personnel. Never give anything by mouth to unconscious personnel. Seek immediate medical attention.  
Allergies, eczema, or skin conditions can be aggravated by this product.

**Section 5: Fire Fighting Measure:**

Flash Point: 112 C (234 F)  
LEL: 1.00 UEL: 13.00

Carbon dioxide, foam, dry chemical, water spray.  
Decomposition and combustion products may be toxic  
Self contained breathing apparatus

**Section 6: Accidental Release Measures**

Absorb onto sand or other absorbent material. Shovel into closed container for disposal. Flush contaminated area with water.

**Section 7: Handling and Storage**

Causes severe eye irritation and may cause eye burns. Can cause skin irritation.  
May be harmful if swallowed. Avoid vapor or mist. Avoid skin contact. Wash thoroughly after handling. Overexposure can have effects on nervous system.  
Store in closed containers.

**Section 8: Exposure Controls/ Personal Protection**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Benzyl Alcohol 100-51-6	Not Established	Not Established	Not Established
Modified Polyamine 1477-55-0	Not Established	0.1 mg/m3 Ceiling	NIOSH: 0.1 mg/m3 Ceiling

Good general mechanical ventilation and local exhaust.  
Assure personnel safety training.  
Wear protective equipment to prevent exposure and personal contact.  
Wear impervious gloves  
Use NIOSH approved vapor respirator if required.  
Wear splash proof goggles.  
Wash cloths before reuse. Dispose of contaminated shoes.

**Section 9: Physical and Chemical Properties**

<b>Viscosity:</b> N/A <b>Appearance:</b> N/A <b>Vapor Pressure:</b> 0.025 mmHg <b>Vapor Density:</b> 3.7 <b>DENSITY</b> 9.03 <b>Freezing point:</b> N/A <b>Boiling range:</b> 205°C <b>Evaporation rate:</b> N/A <b>Explosive Limits:</b> N/A  <b>Autoignition temperature:</b> N/A	<b>Coating VOC Lb/Gal</b> 0.00 <b>Odor:</b> N/A <b>Odor threshold:</b> N/A <b>pH:</b> N/A <b>Melting point:</b> N/A <b>Solubility:</b> N/A <b>Flash point:</b> 234 F, 112 C <b>Flammability:</b> N/A <b>Partition coefficient (n- octanol/water):</b> N/A <b>Decomposition temperature:</b> N/A
---	--

**Section 10: Stability and Reactivity**

These materials are stable. Under normal conditions of storage and use hazardous reactions or polymerization will not occur.  
 Avoid all source of ignitions, sparks or flames. Do not allow vapor to accumulate in low lying areas.

STABLE

Do not expose to strong oxidizing agents or strong acids.

Under normal use, no hazardous decomposition products are produced.

Hazardous polymerization will not occur.

**Section 11: Toxicological Information**

**Mixture Toxicity**

Oral Toxicity LD50: 1,298mg/kg  
 Dermal Toxicity LD50: 2,742mg/kg  
 Inhalation Toxicity LC50: 18mg/L

Routes of Entry:

**Ingestion**

Exposure to this material may affect the following organs:

**Eyes      Kidneys      Liver      Skin      Respiratory System**

**Effects of Overexposure**

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
-------------------	--------------------	-----------------	--------------------------

**Section 12: Ecological Information**

None available.

**Component Ecotoxicity**

Benzyl Alcohol      96 Hr LC50 Pimephales promelas: 460 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 10 mg/L [static]  
 48 Hr EC50 water flea: 23 mg/L

**Section 13: Disposal Considerations**

Dispose in accordance with federal, state, and local regulations.

**Section 14: Transport Information**

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	PAINT			
IATA	PAINT			

**Section 15: Regulatory Information**

MASSACHUSETTS RIGHT TO KNOW

1477-55-0 Modified Polyamine 20 to 30 %

100-51-6 Benzyl Alcohol 40 to 50 %

NEW JERSEY RIGHT TO KNOW

1477-55-0 Modified Polyamine 20 to 30 %

PENNSYLVANIA RIGHT TO KNOW

1477-55-0 Modified Polyamine 20 to 30 %

100-51-6 Benzyl Alcohol 40 to 50 %

100-51-6 Benzyl Alcohol

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
----------------	-------------------	------------------------------

**EU Risk Phrases**

**Safety Phrase**

- None

**Section 16: Other Information**

HMIS and NAFTA rating are on a 0 to 4 rating scale with 0 minimal hazard, and 4 represent significant danger or hazard.

**Hazardous Material Information System (HMIS)**

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>PERSONAL PROTECTION</b>	<b>G</b>

**HMIS & NFPA Hazard Rating**

**Legend**

\* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

**National Fire Protection Association (NFPA)**



The information provided herein was believed by Induron Protective Coating to be accurate and reliable, but the user is responsible to comply with all laws and procedures whether included or not. Induron makes no warranty expressed or implied concerning the accuracy of the information except the product will comply with Induron specifications.

Date Prepared: 9/22/2016