### SAFETY DATA SHEET

### Section 1: Manufacturer's Identification

Product Name: E-BOND 100 PART A Product Code: D-1008

Manufacturer's Name: Induron Protective Coatings, LLC

Address: 3333 Richard Arrington Blvd. N. Birmingham, Alabama 35234

Emergency Phone: 1-800-424-9300 Information Phone: (205)324-9584

### Section 2: Composition / Information on Ingredients

### **GHS Ratings:**

Dermal Toxicity

Skin corrosive

2

Reversible adverse effects in dermal tissue, Draize score:
>= 2.3 < 4.0 or persistent inflammation

Eye corrosive

2A

Eye irritant: Subcategory 2A, Reversible in 21 days

Skin sensitizer 1 Skin sensitizer

Reproductive toxin 1A Based on human evidence

**GHS Hazards** 

H311 Toxic in contact with skin
H315 Causes skin irritation
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation

H360 May damage fertility or the unborn child

**GHS Precautions** 

P201

P202 Do not handle until all safety precautions have been read and understood
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash equipment and contaminated skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Use personal protective equipment as required

Obtain special instructions before use

P312 Call a POISON CENTER or doctor/physician if you feel unwell
P321 Wash contaminated skin, follow Physician's instructions for treatment.
P322 Specific measures Remove contaminated clothing and protective equipment.

P361 Remove/Take off immediately all contaminated clothing
P362 Take off contaminated clothing and wash before reuse
P363 Wash contaminated clothing before reuse

P302+P352 IF ON SKIN: Wash with soap and water
P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do – continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention P332+P313 If skin irritation occurs: Get medical advice/attention

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P337+P313 Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container in accordance to approriate regulations and laws.

Signal Word: Danger

SDS for: D-1008 Page 1 of 5



This product can be a skin and eye sensitizer. The material should washed from skin or flushed from eyes immediately. Contaminated clothing should be removed. Wear proper protective equipment. Any other acute toxicalogical information can be found in section 11.

Approximately 2% of the population can develop skin sensitivity with increasing inflamation and allergic reactions with repeated exposure.

#### Section 3: Hazards Identification

Chemical Name	CAS number	Weight Concentration %
Diglycidyl Ether of Bisphenol A	25068-38-6	90.00% - 100.00%

### Section 4: First Aid Measures

Move the exposed person to fresh air. If vapors are still present the rescuer should wear the appropriate mask. If breathing is irregular or arrest occurs use artificial respiration by trained personnel. Loosen tight fitting clothing, Get medical aid immediately.

Immediately flush eyes with plenty of water for at least 15 minutes. Regularly lift upper and lower eyelids during flushing. Remove contact lenses. Get medical aid.

Flush contaminated skin with water. Remove contaminated cloths, avoiding skin contact while doing so. Get medical attention. Clean contaminated shoes thoroughly before reuse.

Wash mouth out thoroughly. Do not induce vomiting unless directed by medical personnel. Get medical attention No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been inhaled or ingested.

### Section 5: Fire Fighting Measures

Flash Point: 248 C (478 F)

LEL: UEL:

For flammable liquid: Can burst from pressure if in sealed container and heated, with risk of subsequent explosion. Vapors are heavier than air, can spread on ground and collect in low lying areas. Runoff to a collection area can create a fire or explosion hazard.

Dry Chemical, CO2, water spray)(fog), or foam. Do not use water jet.

Isolate scene removing persons not trained if there is a firem. Move containers from fire area if there is no risk. Use water spray to keep fire exposed containers cool

Decomposition products man include the following materials: Carbon Oxides.

Fire fighters should wear appropriate protective equipment and wel-contain breathing apparatus.

Use dry chemical, CO2, water spray(fog) or foam. Do not use water jet.

### Section 6: Accidental Release Measures

No action should be taken with untrained personnel. Evacuate surrounding areas. Do not touch or walk through spill. Shut off all ignition sources. Provide adequate ventilation. Use appropriate protective equipment. Do not breath dust, mist, or vapor.

Stop leak if without risk. Move containers form spill area. Dilute with water and mop up if water-soluble, or absorb with inert dry material and place in appropriate waste container. Dispose via licensed waste disposal.

Stop leak if without risk. Move containers from area. Approach from upwing. Prevent run off to water source, basements, sewers, or confined areas. Contain and collect spillage with non combustible, absorbent materials, sand, vermiculite, diatomic earth and dispose by local regulation. Use sark-proof tools and explosion roof equipment.

### Section 7: Handling and Storage

Use appropriate personal protective equipment. No eating, drinking, or smoking in areas of use. Persons with a history of skin sensitization should not be employed in any process in which this product is used. Avoid exposure during pregna ncy. Do not ingest. Use adequate ventilation or respirator. Keep in approriate container avoiding open flames, sparks or other ignition sources. Use explosion proof equipment and non sparking tools. Use proper grounding procedures.

SDS for: D-1008 Page 2 of 5

Store in designated flamable liquid storage areas. Protect from direct sunlight in dry, cool ventilated areas. Keep food and drink away from area. Eliminate all ignition sources. Opened containers must be carefully resealed and kept upright. Do not use unlabled containers. Use appropriate containment.

### Section 8: Exposure Controls/ Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Diglycidyl Ether of Bisphenol A 25068-38-6	Not Established	Not Established	Not Established

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to meet exposure to airborne cotaminates above statutory limits. Use appropriate controls to keep concentration below explosive limits.

Ensure adequate ventalation by standard emmision testing procedures, Use appropriate respiratory equipment when needed.

Assure safety traning of operators in regards to handleing liquids and vapors. Follow local regulatory rules of exposure control using air purifying or air supplied mask as needed.

Use appropriate protective equipment according to OSHA and NAFTA standards and labeling. Ensure eye wash stations and safety showers are available.

Wash contaminated gear and clothing before reuse.

### Section 9: Physical and Chemical Properties

Viscosity: N/A Coating VOC Lb/Gal 0.03 Appearance: N/A Odor: N/A Vapor Pressure: 0.030 mmHg Odor threshold: N/A Vapor Density: 3.1 pH: N/A **DENSITY** 9.75 Melting point: N/A Solubility: N/A Freezing point: N/A Boiling range: 260°C Flash point: 478 F,248 C Flammability: N/A Evaporation rate: N/A Partition coefficient (n- N/A Explosive Limits: N/A octanol/water): Autoignition temperature: N/A Decomposition temperature: N/A

### Section 10: Stability and Reactivity

These materials are stable. Under normal conditions of storatge and use hazardous reactions or polymerization will not

Avoid all source of ignitions, sparks or flames. Do not allow vapor to accumulate in low lying areas.

#### **STABLE**

Do not expose to strong oxidizing agents, strong acids, or alapahtic amines.

Under normal use, no hazardous decomposition products are produced.

Hazardous polymerization will not occur.

### Section 11: Toxicological Information

### **Mixture Toxicity**

Dermal Toxicity LD50: 201mg/kg

Routes of Entry:

Exposure to this material may affect the following organs:

SDS for: D-1008 Page 3 of 5

Printed: 9/20/2016 at 9:48:49AM

### **Effects of Overexposure**

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

CAS Number Description % Weight Carcinogen Rating

N/A None

### Section12: Ecological Information

No known significan effects or critical hazards.

### **Component Ecotoxicity**

### Section 13: Disposal Considerations

Minimize the generation of waste whenever possible. Dispose by license waste disposal contractor. Comply with local. regional, and fedral disposal regulations and legislation.

### Section 14: Transport Information

<b>Agency</b>	Proper Shipping Name	<b>UN Number</b>	Packing Group	<b>Hazard Class</b>
DOT	PAINT	NA	NA	NA
IATA	PAINT	NA	NA	NA

### Section 15: Regulatory Information

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

HAZARDOUS AIR POLLUTANTS

- None

HAZARDOUS SUBSTANCE/CHEMICALS/POLLUTANTS

- None

MASSACHUSETTS RIGHT TO KNOW

- None

**NEW JERSEY RIGHT TO KNOW** 

- None

PENNSYLVANIA RIGHT TO KNOW

- None
- None

**CHEMICAL LIST FOR SARA 311** 

- None
- None

**CHEMICAL LIST FOR SARA 313** 

SDS for: D-1008 Page 4 of 5

Printed: 9/20/2016 at 9:48:49AM

Country Regulation All Components Listed

### **EU Risk Phrases**

### **Safety Phrase**

- None

### Section 16: Other Information

HMIS and NAFTA rating are on a 0 to 4 rating scale with 0 minimal hazard, and 4 represent significant danger or hazard.

### **Hazardous Material Information System (HMIS)**

## rstem (HMIS) National Fire Protection Association (NFPA)



HMIS & NFPA Hazard Rating Legend


\* = Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH



The information provided herein was believed by Induron Protective Coating to be accurate and reliable, but the user is responsible to comply with all laws and procedures whether included or not. Induron makes no warranty expressed of implied concering the accuracy of the infomation except the product will comply with Induron specifications.

Reviewer Revision

Date Prepared: 9/20/2016

SDS for: D-1008 Page 5 of 5

### **SAFETY DATA SHEET**

### Section 1: Manufacturer's Identification

Product Name: E-BOND 100 PART B Product Code: Q-1008

Manufacturer's Name: Induron Protective Coatings, LLC

Address: 3333 Richard Arrington Blvd. N. Birmingham, Alabama 35234

Emergency Phone: 1-800-424-9300 Information Phone: (205)324-9584

### Section 2: Composition / Information on Ingredients

### **GHS Ratings:**

Skin corrosive	1C	Destruction of dermal tissue: Exposure < 4 hours
		Observation < 14 days, visible necrosis in at least one animal
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after
		exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Respiratory sensitizer	1	Respiratory sensitizer
Skin sensitizer	1	Skin sensitizer

### **GHS Hazards**

H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

### **GHS Precautions**

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash equipment and contaminated skin thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P285	In case of inadequate ventilation wear respiratory protection
P310	Immediately call a POISON CENTER or doctor/physician
P321	Wash contaminated skin, follow Physcian's instructions for treatment.
P363	Wash contaminated clothing before reuse
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
	Rinse skin with water/shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable
	for breathing
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in
	a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact
	lenses if present and easy to do – continue rinsing
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physcian.
P405	Store locked up
P501	Dispose of contents/container in accordance to approriate regulations and laws.

Signal Word: Danger

SDS for: Q-1008 Page 1 of 4



### Section 3: Hazards Identification

Chemical Name	CAS number	Weight Concentration %
2,4,6 TRIDIMETHLYAMINOMETHYLPHENOL	90-72-2	5.00% - 10.00%

### Section 4: First Aid Measures

Remove to fresh air, seek medical attention.

Immediately flush eyes with water for at least 15 min. Seek medical attention.

Immediately washs with soap and water. Remove contaminated clothing and

launder before reuse. Destroy contaminated shoes. Seek medical attention.

Do not induce vomiting unless directed by medical personnel. Never give anything by

mouth to unconcious personnel. Seek immediate medical attention.

Allergies, eczema, or skin conditions can be aggrivated by this product.

### Section 5: Fire Fighting Measure:

Flash Point: 101 C (214 F)

LEL: UEL:

Carbon dioxide, foam, dry chemical, water spray.

Decomposition and combustion products may be toxic

Self contained breathing apparatus

### Section 6: Accidental Release Measures

Absorb onto sand or other absorbent material. Shovel into cloased container for disposal. Flush contaminated area with water.

### Section 7: Handling and Storage

Causes sever eye irritation and may cause eye burns. Can cause skin irritation.

May be harmful if swallowed. Avoid vapor or mist. Avoid skin contact. Wash

thoroughly after handling.. Overexposure can have effects on nervous system.

Store in closed containers.

### Section 8: Exposure Controls/ Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
2,4,6	Not Established	Not Established	Not Established
TRIDIMETHLYAMINOMETH			
YLPHENOL			
90-72-2			

Good general mechanical ventilation and local exhaust.

Assure personnel safety training.

SDS for: Q-1008 Page 2 of 4

Wear protective equipment to prevent exposure and personal contact.

Wear impervious gloves

Use NIOSH approved vapor respirator if required.

Wear splash proof goggles.

Wash cloths before reuse. Dispose of contaminated shoes

### Section 9: Physical and Chemical Properties

Viscosity: N/A

Appearance: N/A

Vapor Pressure: N/A

Vapor Density: N/A

**DENSITY** 8.27

Freezing point: N/A

Boiling range: N/A

Evaporation rate: N/A

**Explosive Limits: N/A** 

Autoignition temperature: N/A

Coating VOC Lb/Gal 0.00

Odor: N/A

Odor threshold: N/A

pH: N/A

Melting point: N/A

Solubility: N/A

Flash point: 214 F,101 C

Flammability: N/A

Partition coefficient (n- N/A

octanol/water):

Decomposition temperature: N/A

### Section 10: Stability and Reactivity

These materials are stable. Under normal conditions of storatge and use hazardous reactions or polymerization will not occur. Avoid all source of ignitions, sparks or flames. Do not allow vapor to accumulate in low lying areas.

#### STABLE

Do not expose to strong oxidizing agents or strong acids.

Under normal use, no hazardous decomposition products are produced.

Hazardous polymerization will not occur.

### Section 11: Toxicological Information

#### **Mixture Toxicity**

Oral Toxicity LD50: 3,957mg/kg

Routes of Entry:

Exposure to this material may affect the following organs:

### **Effects of Overexposure**

**CAS Number** Description % Weight Carcinogen Rating

### Section 12: Ecological Information

None available.

### **Component Ecotoxicity**

### Section 13: Disposal Considerations

Dispose in accordance with federal, state, and local regulations.

SDS for: Q-1008 Printed: 9/20/2016 at 9:46:45AM

### Section 14: Transport Information

<b>Agency</b>	Proper Shipping Name	<b>UN Number</b>	Packing Group	<b>Hazard Class</b>
DOT	PAINT	NA	NA	NA
IATA	PAINT	NA	NA	NA

### Section 15: Regulatory Information

Country Regulation All Components Listed

### **EU Risk Phrases**

### **Safety Phrase**


- None


### Section 16: Other Information

HMIS and NAFTA rating are on a 0 to 4 rating scale with 0 minimal hazard, and 4 represent significant danger or hazard.

### **Hazardous Material Information System (HMIS)**

# National Fire Protection Association (NFPA)





The information provided herein was believed by Induron Protective Coating to be accurate and reliable, but the user is responsible to comply with all laws and procedures whether included or not. Induron makes no warranty expressed of implied concering the accuracy of the infomation except the product will comply with Induron specifications.

Reviewer Revision

Date Prepared: 9/20/2016

SDS for: Q-1008 Page 4 of 4