

# SAFETY DATA SHEET

## SECTION 1- MANUFACTURER'S IDENTIFICATION

Product Name: INDURA-GALV PRIMER, GALVANIZE GRAY Product Code: G-8120  
Manufacturer's Name: Induron Protective Coatings, LLC Emergency Phone: 1-800-424-9300  
Address: 3333 Richard Arrington Blvd. N. Information Phone: (205)324-9584  
Birmingham, Alabama 35234

## Section 2 - Composition / Information on Ingredients

### GHS Ratings:

Flammable liquid	3	Flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$ (140°F)
Skin corrosive	3	Reversible adverse effects in dermal tissue, Draize score: $\geq 1.5 < 2.3$
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Mutagen	1B	Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1A	Known Human Carcinogen Based on human evidence
Reproductive toxin	1B	Presumed, Based on experimental animals

### GHS Hazards

H226	Flammable liquid and vapour.
H316	Causes mild skin irritation
H319	Causes serious eye irritation
H340	May cause genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child

### GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash equipment and contaminated skin thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P370+P378	In case of fire: Use CO <sub>2</sub> , water spray, foam, or dry chemical to extinguish.
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool

**Signal Word: Danger**

Preexisting skin, eye, and respiratory disorders may be aggravated by exposure to this product. Impaired kidney and liver functions from preexisting disorders may be aggravated by exposure to this product.

Kidney damage may be evidenced by changes in urine output, urine appearance, or edema (swelling from fluid retention). Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

<b>Section 3 - Hazards Identification</b>
---

Chemical Name	CAS number	Weight Concentration %
Zinc	7440-66-6	10.00% - 20.00%
Titanium Dioxide Colorant	13463-67-7	5.00% - 10.00%
STODDARD SOLVENT	8052-41-3	1.00% - 5.00%
2-ETHYL BENZENE	100-41-4	0.10% - 1.00%
METHYL ETHYL KETONE OXIME	96-29-7	0.10% - 1.00%

<b>Section 4 - First Aid Measures</b>
---------------------------------------

**INHALATION** - If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation; call a physician. Administer oxygen if a qualified operator is available.

**EYE CONTACT** - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

**SKIN CONTACT** - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water.

**INGESTION** - If material is ingested, seek immediate medical attention. If vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs.

Notes to Physician: No data found

<b>Section 5 - Fire Fighting Measures</b>
---

Flash Point: 40 C (104 F)

LEL:

UEL:

**EXTINGUISHING MEDIA:** Use carbon dioxide (CO<sub>2</sub>), "alcohol" foam, dry chemical systems. Direct water application may cause violent frothing.

**UNUSUAL FIRE OR EXPLOSION HAZARDS:** The product may contain linseed oil and represents a spontaneous combustion hazard. To avoid spontaneous combustion soak soiled rags and waste in water immediately after use in a closed metal container.

**HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon and hydrocarbons

**FIRE FIGHTING:** If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure. Use water spray to cool unopened containers.

**FIRE FIGHTING:** If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel

and equipment with a water wash-down after fire and smoke exposure.

**Section 6 - Accidental Release Measures**

**SPILL AND LEAK PROCEDURES:** Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

**SMALL SPILLS:** Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes. Wet absorbant materials with water to prevent spontaneous combustion with alkyd type formulas.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

**LARGE SPILLS:** Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas .

Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes. Wet absorbant with water for alkyd type spills.

**Section 7 - Handling and Storage**

**HANDLING PRECAUTIONS:** Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

**STORAGE:** Prevent from freezing. Do not store above 120 F (49 C).

Store only in original containers.

**REGULATORY REQUIREMENTS:** No data found.

**Section 8 - Exposure Controls / Personal Protection**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Zinc 7440-66-6	Not Established	Not Established	Not Established
Titanium Dioxide Colorant 13463-67-7	15 mg/m3 TWA (total dust)	10 mg/m3 TWA	Not Established
STODDARD SOLVENT 8052-41-3	500 ppm TWA; 2900 mg/m3 TWA	100 ppm TWA	NIOSH: 350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min)
2-ETHYL BENZENE 100-41-4	100 ppm TWA; 435 mg/m3 TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL
METHYL ETHYL KETONE OXIME 96-29-7	Not Established	Not Established	Not Established

**ENGINEERING:** Ensure processing (curing) ovens are properly vented to prevent the introduction of processing

fumes into the workplace. Use explosion-proof equipment and good manufacturing practice.

**VENTILATION:** Use only with adequate ventilation, i.e., ventilation in compliance with occupational exposure limits.

**ADMINISTRATIVE CONTROLS:** No data found.

**PROTECTIVE EQUIPMENT:** Wear splash goggles. If extra protection is required, wear a face shield over the splash goggles. Face shields are effective only if worn in addition to splash goggles.

Wear a chemical-resistant, butyl-rubber apron and other protective clothing, as deemed appropriate, to avoid skin contact with material.

Wear chemical-resistant gloves (butyl rubber or neoprene). Protective gloves should be inspected frequently and discarded when they exhibit cuts, tears, pinholes, or signs of excessive wear.

**CONTAMINATED EQUIPMENT:** Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

### Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

<b>Viscosity:</b> N/A	<b>Coating VOC Lb/Gal</b> 0.57
<b>Appearance:</b> N/A	<b>Odor:</b> N/A
<b>Vapor Pressure:</b> 1.4 mmHg	<b>Odor threshold:</b> N/A
<b>Vapor Density:</b> 3.4	<b>pH:</b> N/A
<b>DENSITY</b> 13.91	<b>Melting point:</b> N/A
<b>Freezing point:</b> N/A	<b>Solubility:</b> N/A
<b>Boiling range:</b> 150°C	<b>Flash point:</b> 104 F, 40 C
<b>Evaporation rate:</b> N/A	<b>Flammability:</b> N/A
<b>Explosive Limits:</b> N/A	<b>Partition coefficient (n- octanol/water):</b> N/A
<b>Autoignition temperature:</b> N/A	<b>Decomposition temperature:</b> N/A

### Section 10 - Stability and Reactivity

Stability:

STABLE

Components of this mixture are incompatible with the following materials:

This mixture is likely to exhibit the following combustion products:

Hazardous polymerization will not occur.

### Section 11 - Toxicological Information

#### Mixture Toxicity

Inhalation Toxicity LC50: 93mg/L

Routes of Entry:

#### Ingestion

Exposure to this material may affect the following organs:

**Eyes      Kidneys      Central Nervous System      Skin      Respiratory System**

#### Effects of Overexposure

**Carcinogenicity:** The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
8052-41-3	STODDARD SOLVENT	1 to 5%	STODDARD SOLVENT: EU REACH: Present (P)
13463-67-7	Titanium Dioxide Colorant	5 to 10%	Titanium Dioxide Colorant: NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed
100-41-4	2-ETHYL BENZENE	.1 to 1.0%	2-ETHYL BENZENE: IARC: Possible human carcinogen OSHA: listed

### Section 12 - Ecological Information

Ecological information: No data found.

#### Component Ecotoxicity

Zinc

96 Hr LC50 Pimephales promelas: 2.16 - 3.05 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 0.211 - 0.269 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 2.66 mg/L [static]; 96 Hr LC50 Cyprinus carpio: 30 mg/L; 96 Hr LC50 Cyprinus carpio: 0.45 mg/L [semi-static]; 96 Hr LC50 Cyprinus carpio: 7.8 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 3.5 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 0.24 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 0.59 mg/L [semi-static]; 96 Hr LC50 Oncorhynchus mykiss: 0.41 mg/L [static]  
 48 Hr EC50 Daphnia magna: 0.139 - 0.908 mg/L [Static]  
 96 Hr EC50 Pseudokirchneriella subcapitata: 0.11 - 0.271 mg/L [static]; 72 Hr EC50 Pseudokirchneriella subcapitata: 0.09 - 0.125 mg/L [static]

2-ETHYL BENZENE

96 Hr LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static]  
 48 Hr EC50 Daphnia magna: 1.8 - 2.4 mg/L  
 72 Hr EC50 Pseudokirchneriella subcapitata: 4.6 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: >438 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L [static]; 96 Hr EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static]

METHYL ETHYL KETONE OXIME

96 Hr LC50 Pimephales promelas: 777 - 914 mg/L [flow-through]; 96 Hr LC50 Poecilia reticulata: 760 mg/L [static]  
 48 Hr EC50 Daphnia magna: 750 mg/L  
 72 Hr EC50 Desmodesmus subspicatus: 83 mg/L

### Section 13 - Disposal Considerations

As the US EPA, state, regional, and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all the requirements which affect you. Dispose of the hazardous waste at a properly licensed and permitted disposal site or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream." Refer to Title 40 of the Code of Federal Regulations, Part 261 (40 CFR 261). This part of the Code identifies solid wastes which are subject to regulation under various sections of the Code and which are subject to the notification requirements of Section 3010 of the Resource Conservation and Recovery Act (RCRA).

**Section 14 - Transport Information**

**Section 14 - Transport Information**

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	PAINT	1263	III	3
IAA	PAINT	1263	III	3

**15: Regulatory Information**

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- 100-41-4 2-ETHYL BENZENE 0.1 to 1.0 %
- 13463-67-7 Titanium Dioxide Colorant 5 to 10 %

**HAZARDOUS AIR POLLUTANTS**

- 100-41-4 2-ETHYL BENZENE

**MASSACHUSETTS RIGHT TO KNOW**

- 100-41-4 2-ETHYL BENZENE 0.1 to 1.0 %
- 8052-41-3 STODDARD SOLVENT 1 to 5 %
- 13463-67-7 Titanium Dioxide Colorant 5 to 10 %
- 7440-66-6 Zinc 10 to 20 %

**NEW JERSEY RIGHT TO KNOW**

- 100-41-4 2-ETHYL BENZENE 0.1 to 1.0 %
- 8052-41-3 STODDARD SOLVENT 1 to 5 %
- 13463-67-7 Titanium Dioxide Colorant 5 to 10 %
- 7440-66-6 Zinc 10 to 20 %

**PENNSYLVANIA RIGHT TO KNOW**

- 100-41-4 2-ETHYL BENZENE 0.1 to 1.0 %
- 8052-41-3 STODDARD SOLVENT 1 to 5 %
- 13463-67-7 Titanium Dioxide Colorant 5 to 10 %
- 7440-66-6 Zinc 10 to 20 %
- 8001-26-1 Linseed oil 30 to 40 %

**CHEMICAL LIST FOR SARA 311/312**

- 8001-26-1 Linseed oil

**CHEMICAL LIST FOR SARA 313**

- 100-41-4 2-ETHYL BENZENE

**Country**

**Regulation**

**All Components Listed**

**EU Risk Phrases**

**Safety Phrase**

- None


**16: OTHER INFORMATION**

**Hazardous Material Information System (HMIS)**

HEALTH	*	2
FLAMMABILITY		2
PHYSICAL HAZARD		1
PERSONAL PROTECTION		B

**HMIS & NFPA Hazard Rating Legend**  
\* = Chronic Health Hazard  
0 = INSIGNIFICANT  
1 = SLIGHT  
2 = MODERATE  
3 = HIGH

**National Fire Protection Association (NFPA)**



Date Prepared: 10/18/2016

Reviewer Revision